

# AP / SP SERIES Price Computing Scale

Commercial Scale



AP-1



SP-1

## FEATURES

- 28 PLU memory
- Daily total scales report

## SPECIFICATIONS

Model	AP Series
Weighing Capacity	6 × 0.002 kg, 15 × 0.005 kg, 30 × 0.01 kg
Display Digit	6/5/6, 7/5/6 (Total Price/Weight/Unit Price)
Display Designators	Zero and Net
Power Source	AC 110/120/220/240 V, 50/60Hz
Power Consumption	Approx. 10W
Operating Temperature	-10 °C ~ +40 °C
Platter Size (mm)	340(W) × 215(D)
Dimensions (mm)	435(W) × 325(D) × 495(H)
Product Weight	6.5 kg

## OPTIONS

- Display on the rear center
- Dual interval
- kg/lb switchable
- RS-232C interface
- Large platter : 440(W) × 275(D) × 50(H)mm
- Printer connector available
  - EPSON (TM-U300B, TM-L60)
  - DEP-50 (Receipt printer)

## FEATURES

- Rechargeable battery : SP-15BF(VFD), SP-BL(LED)
- Charging / Operating time : 9/25 hours(SP-BL)

## SPECIFICATIONS

Model	SP-1(MX) SP-15BF(MX)	SP-1(EX) SP-15BF(EX)	SP-BL
Weighing Capacity	6 × 0.002 kg, 15 × 0.005 kg, 30 × 0.01 kg		
Display Digit	6/5/6, 7/5/6 (Total/Weight/Unit)		8/5/8 (Total/Weight/Unit)
Display	VFD		LED
Display Designators	Zero, Net and Low battery		
Power Source	AC 110/120/220/240 V, 50/60Hz		
Power Consumption	10W	3W	
Charging Time	10 hours	9 hours	
Operating Time	10 ~ 12 hours	25 hours	
Operating Temperature	-10 °C ~ +40 °C		
Platter Size (mm)	372(W) × 278(D)		
Dimensions (mm)	388(W) × 364(D) × 163(H)	480(W) × 364(D) × 490(H)	
Product Weight	7.2 kg	7.8 kg	

## OPTIONS

- Fish platter (SP-1 MX)
- RS-232C interface
- kg/lb switchable