

IMAGETEAM™ 4800 SR/SF *Industrial 2D Area Imager*



Features

Powered by Adaptus™ imaging technology - Delivers extraordinary reading performance to enable ease-of-use and reader versatility.

Aggressive, omni-directional point-and-shoot reading of linear, PDF417, and full 2D matrix symbols offers ease-of-use and greater throughput.

Rugged Packaging – Impact absorbent, shock resistant housing withstands fifty 6.5 foot (2 meter) drops, and is sealed to resist dust, water, and contaminants from entering the unit. Backed by an industry leading warranty.

Future-Proofed Technology - The versatility of Adaptus imaging technology serves broad image-based data capture needs today and protects your investment against future application demands.

Advanced Editing Software – Eases the transition to full 2D matrix data acquisition transfer without expensive host software modifications.

Intelligent Aiming Options - Distinctive green aimer provides superior illumination contrast and the familiar laser aimer makes image capture applications fast and intuitive.

The IMAGETEAM™ 4800 Industrial 2D Area Imager is the first hand held area image reader powered by Adaptus™ Imaging Technology. Adaptus technology decodes faster, farther, and future-proofs your investment. This means your workers spend less time trying to capture data, and more time using this data to make your business more cost efficient.

Whether your application is reading conventional linear bar codes or tomorrow's 2D matrix symbolologies, the IT4800 can capture them all today. If your application requires signature capture, OCR, or digital photography, the IT4800 can do it. Its advanced imaging optics software quickly and easily determines the image content and transfers it to your host system. In fact, full image transfer can be accomplished in less than one second through its on-board full speed USB interface.

The IT4800 can be used in a wide range of applications from circuit board manufacture to package delivery tracking. In addition, bar codes, images, and signature capture can provide positive proof of delivery. If discrepant material needs to be viewed by a production supplier, images can be captured and quickly transferred for immediate review and resolution, saving time and money.

Because these applications often contain challenges for many image capture devices, we have made the IT4800 extra tough. Full shock-absorbing rubber protects the imager from dozens of 6.5 feet (2 meter) drops to concrete. Many application environments exhibit airborne dust and rain, so we have sealed the IT4800 so these elements will not degrade performance. In addition to an IP54 enclosure specification, the IT4800 is backed by an industry leading warranty.

For applications that demand superior aiming, the IT4800 is the best choice. Integrated LED and laser aiming ensures the best aimer visibility for exceptional point-and-shoot performance. This ensures your operator will find and capture the correct image every time.

For additional information, contact your Hand Held Products representative at any of the locations listed on the back, or visit us at www.handheld.com. Call today and see how Hand Held Products' new area imagers measure up!

IMAGETEAM™ 4800 SR/SF Specifications

Performance

Aiming:

Red Laser Aimer: 756nm ±40nm
Green LED Aimer: 520nm ±30nm

Image: VGA, 640x480. Binary, TIFF, or JPEG output.

Working Range:

	8 mil Linear (.020cm)	13 mil UPC (.033cm)	6.6 mil PDF417 (.017cm)	10 mil PDF417 (.025cm)	15 mil Data Matrix (.038cm)	35 mil MaxiCode (.089cm)
IT4800SR						
Near	2.9 in. (7.4cm)	1.9 in. (4.8cm)	3.9 in. (9.9cm)	2.5 in. (6.4cm)	3.1 in. (7.9cm)	1.4 in. (3.6 cm)
Far	7 in. (17.8cm)	11.9 in. (30.2cm)	5.7 in. (14.5cm)	8.4 in. (21.3cm)	5.9 in. (15cm)	12.4 in. (31.5cm)
IT4800SF						
Near	1.9 in. (4.8cm)	1.7 in. (4.3cm)	2.2 in. (5.6cm)	1.4 in. (3.6cm)	1.7 in. (4.3cm)	1.7 in. (4.3 cm)
Far	5.9 in. (15cm)	8.3 in. (21.1cm)	5.4 in. (13.7cm)	7 in. (17.8cm)	5.4 in. (13.7cm)	5.4 in. (13.7cm)

Skew Angle: ±40°

Pitch Angle: ±40°

Horizontal Velocity: 2 in. (5 cm) per second

Mechanical/Electrical

Dimensions

Length: 5.3 in. (13.5 cm)

Height: 6.4 in. (16.3 cm)

Width: 3.2 in. (8.1 cm)

Weight: 7.5 oz. (213 g)

Housing: UL 94V0 grade

Power Requirements: 4.5 - 12Vdc at scanner

Current Draw (Typical):

Green LED Aimer:

Input	Scanning	Idle
5 V	382mA	53mA

Red Laser Aimer:

12 V	157mA	44mA
5 V	372mA	53mA
12 V	157mA	44mA

Power Supply

Noise Rejection: Maximum 100mV peak to peak, 10 to 100 kHz

Environmental

Temperature

Operating: 14°F to +122°F (-10°C to +50°C)

Storage: -40°F to 140°F (-40°C to +60°C)

Humidity: 0 to 95%, non-condensing

Sealing: IP54 (water and dust resistant)

Mechanical Shock: Operational after 50 drops from 6.5 ft. (2 m) to concrete

Ambient Light: 535 to 100,00 lux (full sunlight)


ESD Protection: Functional after 100 discharges at 15kV

Vibration: Withstands 5G peak from 22 to 300 Hz

Agency: FCC Class B, CE EMC Class B, CE Low Voltage Directive, IEC60825-1 LED Safety: Class 1, UL, cUL listed, TÜV

Laser Classification

Laser Aimer Model only: Class 2 under 21 CFR 1040.10 and 1040.11
1mW max output, 650 nm, EN60825-1: 1994+A11+A2
per MIL-HDBK-217F Ground Benign exceeds 82,000 hours



MTBF:

Symbologies

2 Dimensional: PDF417, MicroPDF417, MaxiCode, Data Matrix, QR Code, Aztec, Aztec Mesas, Code 49, and EAN•UCC Composite.

Linear: Codabar, Code 39 including PARAF, Interleaved 2 of 5, Code 2 of 5, Code 11, Code 93, Code 128, UPC, EAN/JAN, RSS.

Postal: Postnet, Planet Code, British Post, China Post, Canadian Post,

Japanese Post, KIX (Netherlands) Post

OCR Fonts: OCR-A, OCR-B

Interfaces: All popular PCs and terminals via keyboard wedge, keyboard replacement/direct connect, TTL level RS-232, TTL level Serial Wedge, USB, wand emulation, HHLC non-decoded laser compatible, True RS-232, IBM 468x, and IBM469x.

Warranty: 5 year warranty

Worldwide Offices

Offices Serving North America
Skaneateles Falls, NY
Tel: +1 315 685 8945
or, in North America: +1 800 582 4263
napresales@handheld.com
Charlotte, NC
Tel: +1 704 998 3998
or, in North America: +1 800 582 4263
napresales@handheld.com

Offices Serving Europe, Middle East, and Africa
Europe
Tel: +31 (0) 40 29 01 600
eupresales@handheld.com
United Kingdom
Tel: +44 (0) 1 925 240055
eupresales@handheld.com
Italy
Tel: +39 (0) 2 67 100752
eupresales@handheld.com

France
Tel: +33 (0) 1 41 158220
eupresales@handheld.com
Germany
Tel: +49 (0) 7 477 151377
eupresales@handheld.com
Spain
Tel: +34 93 228 78 68
eupresales@handheld.com

Offices Serving Asia and the Pacific Rim
Hong Kong
Tel: +852 2511 3050
appresales@handheld.com
Japan
Tel: +813 5770 6312
appresales@handheld.com
Offices Serving Latin America
Naples, Florida
Tel: +1 239 263 7600
lapresales@handheld.com

São Paulo
Tel: +55 11 5016 3454
lapresales@handheld.com
Rio De Janeiro
Tel: +55 21 2176 0250
lapresales@handheld.com
Mexico
Tel: +52 55 5203 2100
lapresales@handheld.com

Web Site Address www.handheld.com

Hand Held Products, Inc., ("Hand Held Products") © 1999-2004. All rights reserved. Printed in the U.S.A.

Due to Hand Held Products' continuing product improvement programs, specifications and features herein are subject to change without notice.